









BLAZOL TITANIUM SYNTH 4T 10W-30 (API:SM)

Description

BLAZOL TITANIUM SYNTH 4T 10W-30(API:SM) is one of the most trusted engine oil. BLAZOL TITANIUM SYNTH 4T 10W-30: SM uses modern additive technology to provide superior protection to extend the life of your engine.

Applications

BLAZOL TITANIUM SYNTH 4T 10W-30(API:SM) is Exceeds engine manufacturer's warranty requirements for gasoline, LPG, CNG or NGV gas engines including turbo, multi-valve passenger cars and catalytic coverters requiring an API SN, SM, SL or SJ lubricant.

> Performance Standards

- API SN
- ILSAC GF5
- GM 6094M

Product Features & Benefits

- Unique technology provides superior deposit protection
- Maximum viscosity against viscosity and thermal breakdown Helps extend engine life Ultra-low friction to improve gas mileage
- When tested in engines with a high level of deposits Sequence VG sludge test.
- protects against the formation of new ones for an up to 40% improved protection against as compared to demanding industry standards

+91 9904403467 info@nickpetrochem.in www.nickpetrochem.in

Lube Lic. No.: DIC/Valsad/LUB.License/Manu/381/2022

IAF















PROPERTIES	TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Color ASTM	Visual	L<2.5
DENSITY @ 29.5°C, gm/cc	ASTM D4052	0.850-0.870
Kinematic Viscosity @ 40°C, cSt	ASTM D445	65-75
Kinematic Viscosity @ 100°C, cSt	ASTM D445	10.5-11.5
Viscosity Index, Min.	ASTM D2270	>130
Flash Point, °C	ASTM D92	>230
Pour Point, ^o C	ASTM D97	<-30
Total Base Number, mg KOH/gm	ASTM D2896	6-8

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.

+91 9904403467 info@nickpetrochem.in www.nickpetrochem.in



CERTIFIED BY: