











## **Description**

BLAZOL STORM Synth 4T 15W50 is premium quality motor cycle engine oil made to cater to the highly demanding lubrication requirements of modern 4-Stroke geared bikes. STORM Synth 15W50 provides superior protection for engine, clutch and gears of the high powered Motor Cycles, especially those withengine displacement of 350 cc and above.

### **Applications**

STORM Synth 15W50 is recommended for all the models of geared 4-Stroke bikes manufactured by RoyalEnfield, viz. Thunderbird 500, Thunderbird 350, Classic Desert Storm 500, Classic 500, Classic 350, Bullet Electra Twin spark, Bullet 350 etc.

### **Performance Standards**

- API SN
- JASO MA2

# > Product Features & Benefits

- Superior thermo-oxidative stability minimizes deposits & sludge build-up and reduces oil thickening, thereby facilitating extended oil life.
- Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improve drivability.
- Exceptional antiwear properties protect vital engine and gear components leading to reduced maintenance
- Excellent thermal and oxidation stability for heavy duty application.
- Effective rust and corrosion inhibition property ensures longer life of critical engine components.

+91 9904403467 info@nickpetrochem.in www.nickpetrochem.in















## **TECHNICAL SPECIFICATIONS**: STORM SYNTH 4T 15W50

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Kinematic Viscosity @ 100°C, cSt	D445	17.5-18.5
Viscosity Index	D2270	140
Kinematic Viscosity @ 40°C, cSt	D445	130-140
Flash Point, °C, min	D92	232
Pour Point OC, max	D97	(-) 21
TBN, mg. KOH/gm.	D2896	6.5-8

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

### **STORAGE**

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

## **ENVIRONMENT, HEALTH AND SAFETY**

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point.
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.

Lube Lic. No.: DIC/Valsad/LUB.License/Manu/381/2022

• Avoid contact with skin and eyes. After skin contact, wash with water and soap.



+91 9904403467 info@nickpetrochem.in www.nickpetrochem.in

