











Description

BLAZOL NEXUS 4T 20W-40 (API-SJ) is high performance, 4-stroke motorcycle engine oil specially developed for new generation motorcycles. It is formulated with premium quality base stocks and superior additive technology which provides enhanced anti-oxidancy, deposit and wear control.

> Applications

Recommended for recommended for 4-stroke motorcycles of all leading OEM's recommending SAE 20W-40 grade engine oil.

Performance Standards

- API SJ
- JASO MA2

> Product Features & Benefits

- Excellent control on Engine wear and deposits.
- It ensures seamless and efficient clutch operation.
- It minimizes friction, leading to improved engine efficiency.
- It Keeps engine parts clean, contributing to a longer engine
- Guarantees good lubrication in normal service conditions.
- Increased oil drain interval due to good thermal resistance
- Retention of viscosity over vide temperature ranges.

+91 9904403467 info@nickpetrochem.in www.nickpetrochem.in

IAF



CERTIFIED BY:











> TECHNICAL SPECIFICATIONS : BLAZOL NEXUS 4T 20W-40 (API -SJ)

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Kinematic Viscosity @ 100°C, cSt	D445	13.5-14.5
Viscosity Index, Min	D2270	128
Kinematic Viscosity @ 40°C, cSt	D445	98-108
Flash Point, °C, min	D92	220
Pour Point OC, max	D97	(-) 20
TBN, mg. KOH/gm.	D2896	4-5

The above details are typical results of normal production and variations in these characteristics may occur. The information contained herein is subject to change without notification. All recommendations and suggestions are without guarantee and the manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty.

> STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.

ENVIRONMENT, HEALTH AND SAFETY

- Do not dispose the used oil to soil, drains and water. Dispose the used oil through authorized collection point.
- This product is unlikely to present any safety & health hazard when properly used in the recommended application.
- Avoid contact with skin and eyes. After skin contact, wash with water and soap.



+91 9904403467 info@nickpetrochem.in www.nickpetrochem.in

Lube Lic. No.: DIC/Valsad/LUB.License/Manu/381/2022





CERTIFIED BY:

